

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015321 A1

(51) International Patent Classification: **G03G 15/20**

Susumu [JP/IP]; 10-30-A201, Edanishi 2-chome, Aoba-ku, Yokohama-shi, Kanagawa 2250014 (JP).

(21) International Application Number: PCT/JP2004/011572

(74) Agent: ITOH, Tadahiko; 32nd Floor, Yebisu Garden Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo 1506032 (JP).

(22) International Filing Date: 5 August 2004 (05.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-290108 8 August 2003 (08.08.2003) JP
2004-209309 16 July 2004 (16.07.2004) JP

(71) Applicant (for all designated States except US): **RICOH COMPANY, LTD.** [JP/IP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo 1438555 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **MATSUSAKA,**

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: **IMAGE FORMING APPARATUS WITH ANOTHER SECONDARY POWER SUPPLY.**



(57) Abstract: An image forming apparatus (1) is disclosed, including: a fixing unit (5); a main power supply (6) that provides a portion of the heaters with voltage; and a secondary power supply (711, 712) that provides another portion of the heaters connected to the portion of the heaters in parallel with power provided by the main power supply. The secondary power supply is disposed below and in the neighborhood of the fixing unit. An electric double layer capacitor (711) of the secondary power supply may be disposed between a side face of a chassis of the image forming apparatus and a thermally insulating wall (713) towards the fixing unit, or at an exterior of the chassis of the image forming apparatus on the side face of the chassis. The secondary power supply thus will not be heated by the fixing unit.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.